

## UC-PW/317

### Prepack Controller/Printer

#### UC-PW

<b>Capacity (Ext. Scale)</b>	50 x .01 lb or 20 x .005 kg
<b>Operator Display</b>	Touchscreen; 10.4 inch Color LCD backlit display with built-in touch keyboard and adjustable angle.
<b>Presets</b>	Unlimited
<b>Network Interface</b>	Wired Ethernet RJ45 Connector or Wireless RF
<b>Processor</b>	ATOM N270
<b>Operating System</b>	Windows® or Linux OS available.
<b>Approvals</b>	UL 60950-1 Information Technology. CSA 22.2-60950-1 Information Technology NIST NTEP requirements for Class III weight device. NTEP/California ECR General Code Requirements. FCC Conducted Emissions and Radiated Emissions for a Class A device. NTEP Certificate of Conformance DOC 02-127A1 NCWM
<b>Operating Temperature</b>	10°C to 40°C (50°F to 104°F), humidity from 5% to 95% noncondensing.
<b>Memory/Storage</b>	1 Gig RAM, 160 G HDD (min)
<b>Power</b>	120 VAC, 100 VAC to 264 VAC, 50/60 Hz, 2.2 Amps, 0.265 kVA
<b>Shipping Weight</b>	15.2 lb (6.9 kg)



#### 317 Printer



<b>Application Modes</b>	Manual and automatic application versions available in data label and DayGlo label configurations
<b>Printing Speed</b>	Fast print speed; 125mm/second (4.9 inches/second)
<b>Label Types</b>	Standard thermal labels. Prints safe handling, nutrition facts and DayGlo merchandizing labels
<b>Label Capacity</b>	Large label capacity; 10" roll with up to 5,000 labels
<b>Max Label Size</b>	130mm (5.1 inches) long x 67mm (2.63 inches) wide
<b>Label Size, Manual Application</b>	Manual application; standard data and Nutrifacts labels from 1.9in. (48mm) to 5.1 inches (130mm) long and up to 2.63 inches (67mm) wide. Barcode or DayGlo labels; lengths from 0.9 inches (23mm) to 1.5 inches (38mm).
<b>Label Size, Automatic Application</b>	Automatic systems; the price label applicator can apply 2.63 inch (67mm) wide labels with lengths of 1.9 inches (48mm) to 4.2 inches (106mm). DayGlo labels; 1.56 inch (40mm) wide labels with lengths from 0.9 inches (23mm) to 1.5 inches (38mm).
<b>Product Conformance</b>	The Model 317 is ETL listed by ETL Testing Laboratories, Inc. and is tested to UL 1950 and CSA C22.2 950-93.
<b>Dimensions</b>	36.8cm (14.5 inches) deep, 20.6cm (8.1 inches) wide and 41.9cm (16.5 inches) tall.
<b>Construction</b>	Stainless steel covers with aluminum base.
<b>Shipping Weight</b>	50 lb (22.7 kg)

Quality certificate ISO 9001  
Environment certificate ISO 14001  
Internet: <http://www.mt.com>  
Worldwide service

Subject to technical changes  
© 2013 Mettler-Toledo, LLC

RT1200.3E

**METTLER TOLEDO**